
Cookiecutter for Birdhouse Documentation

Release 0.3.0

Birdhouse

Sep 05, 2018

Contents:

1	Features	3
2	Installation	5
3	Usage	7
4	Development	9
5	Bump a new version	11

A Cookiecutter template for a Birdhouse bird package

Cookiecutter is a command-line utility to create projects from templates. This *cookiecutter-birdhouse* template creates a barebone PyWPS server adhering to Birdhouse conventions. It comes complete with a framework for installation, configuration, deployment, documentation and tests. It even includes a `Dockerfile` for containerization! Create your project then get started writing new WPS processes in minutes.

- GitHub repo: <https://github.com/bird-house/cookiecutter-birdhouse/>
- Documentation: <http://cookiecutter-birdhouse.readthedocs.io/en/latest/>
- Free software: BSD license

<p>Warning: This is the cookiecutter template for PyWPS <i>without</i> the Buildout deployment. The template for the Buildout deployment is on branch 0.2.x.</p>

CHAPTER 1

Features

- Ready-made PyWPS server (a bird)
- Pre-configured `.travis.yml` for [Travis-CI](#) automated deployment and testing
- Pre-configured `.codacy.yml` for automated [Codacy](#) code review
- A `Dockerfile` and `docker-compose.yml` for containerization
- Preconfigured [Sphinx](#) documentation that can be hosted on [ReadTheDocs](#)
- A `Makefile` to install the code, start, stop and poll the server and more

CHAPTER 2

Installation

Prior to installing cookiecutter-birdhouse, the cookiecutter package must be installed in your environment. This is achieved via the following command:

```
$ conda install -c conda-forge cookiecutter
```

With cookiecutter installed, the cookiecutter-birdhouse template can be installed with:

```
$ cookiecutter https://github.com/bird-house/cookiecutter-birdhouse.git
```

Once cookiecutter clones the template, you will be asked a series of questions related to your project:

```
$ full_name [Full Name]: Enter your full name.

$ email [Email Address]: Enter your email address.

$ github_username [bird-house]: Accept the default or enter your github username.

$ project_name [Babybird]: The name of your new bird.

$ project_slug [babybird]: The name of your bird used as Python package.

$ project_short_description [Short description]: Enter a short description about your ↵
↵project.

$ version [0.1.0]: Enter the version number for your application.

$ http_port [5000]: The HTTP port on which your service will be accessible.

$ https_port [25000]: The HTTPS port on which your service will be accessible.

$ output_port [8090]: The HTTP port on which your service outputs will be accessible.
```


CHAPTER 3

Usage

After answering the questions asked during installation, a *bird* Python package will be created in your current working directory. This package will contain a configurable PyWPS service with some initial test processes.

Then:

- Create a repo and put it there.
- Add the repo to your [Travis-CI](#) account.
- Add the repo to your [ReadTheDocs](#) account + turn on the ReadTheDocs service hook.

For more details, see the [cookiecutter-pypackage](#) tutorial.

See the [babybird](#) example of a generated bird.

CHAPTER 4

Development

If you want to extend the cookiecutter template then prepare your development environment as follows:

```
# clone repo
$ git clone git@github.com:bird-house/cookiecutter-birdhouse.git

# change into repo
$ cd cookiecutter-birdhouse

# create conda environment
$ conda env create -f environment.yml

# activate conda environment
$ source activate cookiecutter-birdhouse

# run tests
$ make test

# bake a new bird with default settings
$ make bake

# the new "baked" bird is created in the cookies folder
$ ls -l cookies/
babybird

# well ... you know what to do with a bird :)

# finally you may clean it all up
$ make clean
```

Bump a new version

Make a new version of this Cookiecutter in the following steps:

- Make sure everything is commit to GitHub.
- Update `CHANGES.rst` with the next version.
- Dry Run: `bumpversion --dry-run --verbose --new-version 0.3.1 patch`
- Do it: `bumpversion --new-version 0.3.1 patch`
- ... or: `bumpversion --new-version 0.4.0 minor`
- Push it: `git push --tags`

See the [bumpversion](#) documentation for details.